



## Kentucky Electric Steel Published Rolling Schedule



P.O. Box 2119 -- Ashland, KY 41105-2119 -- 606-929-1200 -- 800-333-3012

Placing your orders as early as possible helps KES remain on schedule and provide the highest levels of service. Thank you for this consideration.

Please allow up to one week after rolling for shipment

Date Issued	Week of	1/23	1/30	2/6	2/13	2/20	2/27	3/6	3/13	3/20	3/27	4/3	4/10	4/17	4/24
1/11/2017	Roll No.	095	095	095	095	095	095	095	096	096	096	096	096	096	096

### Square Edge Flats

Widths	Thickness														
12" - 11"	1/4 - 2"	INQUIRE							OPEN						
10" - 9"	1/4 - 2"	INQUIRE							OPEN						
8 1/2" - 8"	1/4 - 2"	INQUIRE							OPEN						
7 1/2" - 6 1/8"	1/4 - 2"		INQUIRE							OPEN					
8" - 7"	2 1/4 - 2 1/2"		INQUIRE							OPEN					
6 - 4"	2 1/4 - 3"		INQUIRE							OPEN					
3 1/2"	2 1/4 - 2 1/2"		INQUIRE							OPEN					
6 - 3"	1 1/2 - 2"		INQUIRE							OPEN					
2 1/2"	1-1/2 - 2"			INQUIRE							OPEN				
2"	1-1/2"			INQUIRE							OPEN				
6"	1/4 - 1 1/4"			INQUIRE							OPEN				
5 3/4 - 5"	1/4 - 1 1/4"				INQUIRE							OPEN			
4 3/4 - 4"	1/4 - 1 1/4"				INQUIRE							OPEN			
3 3/4 - 3"	1/4 - 1 1/4"					OPEN							OPEN		
2-3/4 - 2"	1/4 - 1 1/4"						OPEN	OPEN						OPEN	OPEN
1-1/2" - 1-3/4"	1"						OPEN	OPEN						OPEN	OPEN

### Round Edge Flats Including Leaf Spring Flats

Widths	Thickness														
6" REOA	1 1/2"								OPEN						OPEN
6"	1.75" - .375								OPEN						OPEN
5"	1.75" - .375								OPEN						OPEN
4 1/2"	1.75" - .375								OPEN						OPEN
4"	1.75" - .360								OPEN						OPEN
3 1/2"	1.75" - .360								OPEN						OPEN
3"	1.75" - .360								OPEN						OPEN
2 1/2"	1" - .292								OPEN						OPEN



Please allow up to one week after rolling for shipment

We welcome you to contact our sales office with any questions you may have with regards to availability of sizes and grades.  
Additional processing available such as heat treating, straightening, saw cutting and shot blast and oiling

**Thank you for considering Kentucky Electric Steel for your steel product requirements!**

